

## BARNIER<sup>®</sup> 2500

### Polyethylene Adhesive Tape

#### DESCRIPTION

Scapa 2500 is a polyethylene film coated with an acrylic adhesive system. Scapa 2500 is green.

#### APPLICATIONS

- Temporary savings on rough support such as stone, concrete, brick ...
- Savings in paint and plaster protection
- Protection during renovation operations, facade cleaning ...

#### PRODUCT BENEFITS

- Very good adhesion on rough and difficult surfaces (wood, stone, facing, etc.)

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2	N/cm	AFERA 4001
Elongation at Break	200	%	AFERA 4005
Service Temperature	60	°C	Scapa
Tensile Strength	15	N/cm	AFERA 4004
Total Thickness	0.82	mm	AFERA 4006

Note:

**\*\*\*This will be taken from the core product for the SAP Material Group\*\*\***

## STANDARD PRESENTATIONS

- Dimension : 33mx300mm; 33mx500mm
- Packaging: 6; 6
- Core: 76 mm Scapa

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.