

BARNIER® 1253

Low Noise BOPP Packaging Adhesive Tape

DESCRIPTION

Scapa 1253 is a 28 μ micron bi-axially oriented polypropylene film coated with a water based acrylic adhesive system, with 46 total thickness and recommended for general bundling and packaging applications.

APPLICATIONS

- Packing and closing cartons
- Pallet wrapping

PRODUCT BENEFITS

- Silent flow
- Good aging and good resistance to U.V.
- Not cold-breaking
- Moisture and chemical resistant.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +60°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.1	N/cm	AFERA 5001
Elongation at Break	150	%	AFERA 5004
Tensile Strength	42	N/cm	AFERA 4004
Total Thickness	0.046	mm	AFERA 5006

Note:

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

- Colours: Buff, Transparent and White
- Core: 76 mm Scapa branded cardboard core
- Packaging: Flat shrink pack
- Roll Length: 66, 100 and 132 metres
- Roll Width: 50 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.