



Page: 1 of 2

## **BARNIER ® 2702**

# **PVC Premium Electrical Adhesive Tape**

#### **DESCRIPTION**

Barnier 2702 is a 0.13mm premium quality, electrical self-extinguishing soft PVC tape that uses an aggressive pressure sensitive rubber-based adhesive system. It has been designed for use where a recognised specification or international standard is required and where environmental safety is a concern.

#### **APPLICATIONS**

- Hand application
- Primary electrical insulation
- Harnessing
- Protection for low and medium voltage cable splices
- Colour coding.

### **PRODUCT BENEFITS**

- Good resistance to abrasion, corrosion and moisture.
- High dielectric strength and good mechanical protection
- Outstanding conformability
- Tape can be applied at low temperature (till -10°C)
- IMQ and VDE Approval Certificates according to IEC 60454-3-1
- Conforms to the European Directive 2011/65/EC (RoHS 2) and Commission Delegated Directive (EU) 2015/863 (RoHS 3)
- Index temperature 0°C to 90°C

Version: 20 Generated Date: 04 November 2025

www.scapaindustrial.com Product Code: 2702

#### **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Thickness	0.13	mm	IEC 60454-2
Tensile Strength	25	N/cm	IEC 60454-2
Elongation at Break	180	%	IEC 60454-2
Adhesion to Steel	1.8	N/cm	IEC 60454-2
Adhesion to Backing	1.8	N/cm	IEC 60454-2
Dielectric Strength	40	kV/mm	IEC 60454-2
Flammability	Self extinguishing	-	IEC 60454-2

#### STANDARD PRESENTATIONS

Roll Length: 10, 20, 25 and 33metresRoll Width: 12, 15, 19 and 25mm

• Core: 32mm Barnier branded cardboard core

• Packaging: Cellowrapped with Barnier label and bar code

• Colours: Black, White, Grey, Red, Blue, Yellow, Dark green, Light Green, Brown, Orange, Violet, Transparent, Yellow/green

### **RECOMMENDATIONS**

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +5°c and +25°c. Use within 24 months from the date of manufacturing

The tape should be applied with sufficient tension to ensure an optimum bonding and a minimum of two layers with a half overlap. The final layer should be wrapped with a lower tension to prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 20 Generated Date: 04 November 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 2702