



BARNIER ® 2724

PVC Hazard Warning Adhesive Tape

DESCRIPTION

Scapa 2724 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability. Available in striped colours only.

APPLICATIONS

• special signage, danger zones

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion, and moisture.
- Suitable for indoor and protected outdoor environments.
- High abrasion and mechanical resistance.
- Conformable
- Easy transversal tearability.
- Environmentally friendly technology.
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	1.5	N/cm	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Nominal Thickness	0.16	mm	CEI EN 60454
Tensile Strength	25	N/cm	CEI EN 60454

Version: 18	Generated Date: 17 July 2025	Page: 1 of 2
www.scapaindustrial.com	Product Code: 2724	

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

- Colours: (Striped) Yellow/black, White/red
- Core: 76mm Scapa branded cardboard core
- Packaging: Heat shrink sleeve
- Roll Length: 33 metres
- Roll Width: 50, 75 and 100mm

RECOMMENDATIONS

Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°c and +25°c. Use within 24 months. The tape should be applied with sufficient pressure to ensure optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 18

Generated Date: 17 July 2025

Page: 2 of 2

www.scapaindustrial.com

Product Code: 2724

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.