

## Scapa 2900

### Non Adhesive Hazard Warning Polyethylene Tape

#### DESCRIPTION

Scapa 2900 is a 25µm low density polyethylene film red and white striped and recommended for hazard warning and safety applications.

#### APPLICATIONS

- Hazard warning and safety non adhesive tape.

#### PRODUCT BENEFITS

- Easy to tie by hand.
- Suitable for indoor and protected outdoor environments.
- Service temperature: -0°C to +50°C.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Temperature Fusion	100 - 120	°C	-
Total Thickness	0.25	mm	AFERA 4006

Note:

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

## STANDARD PRESENTATIONS

- Colours: Red and White striped
- Core: 76 mm cardboard core
- Packaging: Bulk
- Roll Length: 100 metres
- Roll Width: 50 mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from

dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under

these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.