



# **Scapa 2901**

## Polyethylene Adhesive Tape

## **DESCRIPTION**

Scapa 2901 is a 0.15mm adhesive polyethylene tape which uses an aggressive pressure sensitive rubber-based adhesive system. Scapa 2901 comes in a colour range of clear, black, white, yellow and grey.

#### **APPLICATIONS**

• Agriculture tape, used for sillage film reparation

#### **PRODUCT BENEFITS**

- Hand tearable
- Resistant to moisture, many chemicals, such as dilute acids and alkalis, and salt solutions.
- Black colour is available for UV resistance
- Halogen-free.
- Temperature resistance 70°C.

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	0.15	mm	BS 3924
Breaking Strength	3.2	daN/cm	BS 3924
Elongation at Break	450	%	BS 3924
Adhesion to Steel	4.1	N/cm	BS 3924
Adhesion to Backing	3.18	N/cm	BS 3924
Dielectric Strength	67	kV/mm	BS 3924

Version: 2 Generated Date: 27 November 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 2901

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

#### STANDARD PRESENTATIONS

Branding: Scapa
Roll Length: 33m
Roll Width: 100mm
Colours: black, white

### **RECOMMENDATIONS**

The tape should recover a few seconds without tension before sticking as an excessive stretching can produce some "creep-back". The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 2 Generated Date: 27 November 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 2901