



Page: 1 of 2

# BARNIER® 297

# PVC Adhesive tape for protection and reparations

## **DESCRIPTION**

Barnier 297 is a plasticized PVC, coated with a rubber adhesive. PVC building. Protection and repair. Made in France.

#### **APPLICATIONS**

- Premium PVC masking for exterior use (7 days)
- For smooth and slightly rough surfaces.
- All repair operations, marking, sealing, protecting, maintaining, tightness

# **PRODUCT BENEFITS**

- 0 ° C bis + 70 ° C Indoor / Outdoor
- 7 days
- Masking with all types of paints
- Hand tearable
- High tack
- Very conformable
- · Water and humidity resistant and barrier

### **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	0.8	N/cm	AFERA 4001
Breaking Elongation	170	%	AFERA 4005
Operating Temperature	0° to +70°	°C	-
Tensile Strength	19	N/cm	AFERA 4004
Total Thickness	0.1	mm	AFERA 4006

Version: 21 Generated Date: 07 December 2025

www.scapaindustrial.com Product Code: 297

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims

this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

#### STANDARD PRESENTATIONS

Branding: ScapaCore: 76mm

• Packaging (a): individual shrink with barcode

• Dimension: 33mx50mm; 33mx75mm

Packaging: 36; 24

#### RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants

Version: 21 Generated Date: 07 December 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 297