

BARNIER® 2994

Outdoor Low-Tack Protection Tape

DESCRIPTION

Scapa 2994 is a single coated Polyethylene film, coated with a rubber based adhesive.
Scapa 2994 is black.

APPLICATIONS

- Long-term protection special aluminum frames (5 weeks), glasses (3 weeks) and sensitive supports. A pre-test is recommended to ensure that the substrates do not deteriorate when removing the adhesive tape

PRODUCT BENEFITS

- Good UV resistance (up to 6 months outside)
- Easy hand tearability
- Easy unwinding
- Resistant to moisture, many chemicals, such as dilute acids and alkalis, and salt solutions.
- Easy, clean removal from the protected article after use
- The tape is suitable for use either indoors or outdoors

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Elongation at Break	360	%	AFERA 4005
Peel Adhesion	1.2	N/cm	AFERA 4001
Tensile Strength	20	N/cm	AFERA 4004
Total Thickness	0.123	mm	AFERA 4006
Unwinding strength	0.8	N/cm	AFERA 4013

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Dimension : 33mx50mm
- Packaging: 36
- Core: 76mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.