



# Technical DATA

## BARNIER ® 6095

### 6095 Orange PVC tape

#### DESCRIPTION

Barnier 6095 is a plasticized PVC coated with a rubber adhesive. Building tape. Multi-purpose. Made in France.

#### APPLICATIONS

- Repair, sealing, sealing, masking, protection, maintenance of tarpaulins and masking films, jointing of tarpaulins ...
- Short-term masking (less than 3 days) on concrete, plaster, metal, plastic, etc.
- Masking during painting operation
- Joining insulation boards coated kraft, glass wool, rock, polystyrene (33mx75mm)

#### PRODUCT BENEFITS

- .Unrolls very easily, despite an aggressive adhesive mass
- .Glue on all surfaces, even dusty or damp
- .Remains conformable and flexible, even at low temperatures in winter
- .Hand tearable
- .Indoor and outdoor use
- .Resistant and impermeable to water and humidity
- .High tack

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	0.125	mm	AFERA 4006
Elongation at Break	200	%	AFERA 4005
Adhesion on Steel	1.2	N/cm	AFERA 4001
Tack (Rolling Ball Method)	0.25	cm	-
Unwind Force	0.8	N/cm	-

## STANDARD PRESENTATIONS

- Branding: Barnier
- Colours: Orange
- Roll Width: 50 and 75 mm
- Roll Length: 33 M

*Note:*

## RECOMMENDATIONS

Rolls should be stored flat on their cut edge, in their original packaging, away from dust, heat, humidity, direct sunlight and solvent fumes, at a temperature between +10 ° C and +30 ° C. Under these conditions, the storage time of rolls in a temperate climate will be at least 12 months old.

Surfaces must be clean, dry, free of dust, grease, oil or any other contaminant. Due to the variety of substrates used by the end user, testing by the end user himself is the safest way to test the substrates before final application.

This product is restricted and can't be promoted outside of certain condition. Please contact relevant product manager.