

## BARNIER® 6098

### Polyolefin adhesive Tape

#### DESCRIPTION

Scapa 6098 is a single sided tape, a polyolefin film coated with a rubber based pressure sensitive adhesive. Scapa 6098 is available in green.

#### APPLICATIONS

- On exterior and interior construction sites: reinforce, repair, seal, protect, bale, maintain or join.
- Glue on concrete, rubble, plasterboard, wood, metals, plastic sheets ..
- Masking before painting or rendering of facades of buildings
- General purpose building tape for repairing, sealing, waterproofing, masking, protection

#### PRODUCT BENEFITS

- Remains conformable and supple at low temperature in winter
- Good initial peel adhesion on polyethylene sheet
- Easy unwind in spite of a very aggressive adhesive
- Can be torn by hand
- Flexible and conformable
- Sticks on all surfaces even when they are dusty or damp

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	1.6	N/cm	AFERA 4001
Elongation at Break	110	%	AFERA 4005
Service Temperature	60	°C	INTERNAL
Tape Thickness	0.120	mm	AFERA 4006
Tensile Strength	18	N/cm	AFERA 4004
Unwinding	1.3	N/cm	AFERA 4013

Version: 28

Generated Date: 07 December 2025

Page: 1 of 2

www.scapaindustrial.com

Product Code: 6098

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

*Note:*

*\*\*\*This will be taken from the core product for the SAP Material Group\*\*\**

## **STANDARD PRESENTATIONS**

- Roll Length: 33 metres
- Roll Width: 50 mm
- Core: 76 mm Barnier
- Packaging: Wrap

## **RECOMMENDATIONS**

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be one year. Usage is recommended within one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.