



BARNIER ® 9060P

3 days Premium Paper masking Adhesive Tape

DESCRIPTION

Scapa 9060P is 120µm semi crepe tape coated with a solvent rubber adhesive system, recommended for all general purpose indoor 60°C masking applications.

APPLICATIONS

- Professional painters and plasters masking tape for indoor use.
- Suitable for all general purpose 60°C (One hour) indoor bonding, holding, sealing and masking applications
- Suitable for both brush and spray air drying paints.
- Application up to 3 days

PRODUCT BENEFITS

- Clean removal at room temperature.
- Good paint flake resistance.
- Good peel adhesion.
- Good resistance to water and chemical agents
- Smooth and controlled unwind.
- Resistant to mild chemicals, lacquers, solvents and water.
- Temperature resistance: +60°C (One hour)

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.2	N/cm	AFERA 5001
Elongation at Break	9	%	AFERA 5004
Tensile Strength	35	N/cm	AFERA 5004
Total Thickness	120	μm	AFERA 5006

Version: 10 Generated Date: 05 November 2025

www.scapaindustrial.com Product Code: 9060P

Page: 1 of 2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

Colours: Natural

Core: 76mm Barnier branded cardboard core
Packaging: Individual shrink with 2 labels

Roll Length: 50 metres

Roll Width: 19, 25, 30, 38 and 50mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, the storage life of the tape in a temperate climate should not exceed 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature as well as the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 45° angle with constant speed.

Due to the diversity of materials employed by the user, tests carried out by the user himself/herself before the final application is the surest way of testing the material

Version: 10 Generated Date: 05 November 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 9060P