

BARNIER[®] 808

General Purpose Polypropylene Double Sided Tape

DESCRIPTION

Scapa 808 is a general purpose double sided tape based on a polypropylene film. The tape is coated on both sides with a synthetic rubber based hot melt system with an 80g/m² yellow double sided siliconised paper release liner, resulting in a total thickness of 0.1mm. Recommended for general purpose bonding, mounting and splicing applications.

APPLICATIONS

- Carpet fixing.
- Floor covering.
- Mounting display items.
- Exhibition stands assembly.

PRODUCT BENEFITS

- Cost effective general purpose bonding and splicing tape.
- Highly conformable.
- High tack.
- Not recommended for direct exposure to sunlight or UV.
- Service temperature: -10°C up to +50°C (withstands shorter periods up to 65°C).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
180° Peel Adhesion	5.0	N/cm	AFERA 5001
Elongation at Break	165	%	AFERA 5004
Liner Thickness	0.07	mm	AFERA 5006
Static Sheer	> 40	Hours	AFERA 5012
Tape Thickness (Without Liner)	0.1	mm	AFERA 5006
Tensile Strength	40	N/cm	AFERA 5004

Note:

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

- Colours: White
- Core: 76mm cardboard
- Dimension : 25mx50mm
- Packaging: 24 roll

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.