BARNIER ® 9060S

Special building straight lines

DESCRIPTION

Barnier 9060S is a semi creped paper with a total thickness of 120µm coated with a solvent-based rubber adhesive.
Adhesive smooth paper 60 ° C.

APPLICATIONS

- 3 days
- Protection and masking in building (painting and projection of coatings)
- Masking paint in industry and car body
- Multi-use in industry
- Suitable for both brush and spray air drying paints.
- Suitable for all general purpose 60ºC indoor bonding, holding, sealing and masking applications

PRODUCT BENEFITS

- Good shear and holding strength.
- No staining.
- Resistant to mild chemicals, lacquers, solvents and water.
- Clean removal at room temperature.
- Smooth and controlled unwind.
- Good peel adhesion.
- Good paint flake resistance.
- Continuous temperature resistance: +60°C.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.2	N/cm	AFERA 5001
Elongation at Break	9	%	AFERA 5004
Tensile Strength	35	N/cm	AFERA 5004
Total Thickness	120	µm	AFERA 5006

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Colours: Natural
- Dimension : 50mx19mm; 50mx25mm; 50mx38mm; 50mx50mm; 50mx75mm
- Packaging: 48; 36; 24; 24; 12
- Core: 76mm Scapa or Barnier branded cardboard core

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate should not exceed 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature as well as the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90°angle with constant speed.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.