

Scapa FR335

High Performance, Strong Aluminium Foil Tape - 50 micron

DESCRIPTION

Scapa 335 is a 50 μ soft aluminium foil coated with an acrylic adhesive system, using a siliconised paper release liner.

APPLICATIONS

- Closing rigid air duct insulation.
- For use as a heat reflector.
- Applications requiring detection by photoelectric equipment.

PRODUCT BENEFITS

- Temperature resistance: -35°C to +120°C
- Very soft and very conformable.
- Easy to tear.
- Same aluminium appearance as air duct.

Accreditation:

Meets the fire resistant requirements of specifications NF P 92 – 501, Fire Class M1, BS476 Part 6 & 7 Category 1, Class O and DIN4102-A2

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	6	N/cm	AFERA 5001
Elongation at Break	3	%	AFERA 5004
Tensile Strength	30	N/cm	AFERA 5004
Total Thickness	90	Microns	AFERA 5006

STANDARD PRESENTATIONS

- Core: Scapa, Barnier
- Packaging: Bulk pack with interleaving.
- Roll Length: 50m
- Roll Width: 50, 75, 100mm

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.